

F11SSEF 75 Ohm Coaxial Cable Drop Cable

1100 CommScope Place
Hickory, NC 28603
(800) 982-1708
(828) 324-2200
Fax: (828) 324-3400
Int'l Fax: (828) 323-4989
www.commscope.com
CommScope Properties, LLC
All Rights Reserved



PRODUCT DESCRIPTION:

BONDED LAMINATED ALUMINUM TAPE, 60% BRAID, LAMINATED ALUMINUM TAPE, 40% BRAID, FLOODED FOR UNDERGROUND, PE JACKET

CENTER CONDUCTOR:

14 AWG COPPER-CLAD STEEL
NOMINAL DIAMETER: 0.064" (1.63 mm)

DIELECTRIC:


GAS EXPANDED POLYETHYLENE
NOMINAL DIAMETER OVER DIELECTRIC: 0.280" (7.11 mm)

SHIELD:

1ST SHIELD: LAMINATED ALUMINUM TAPE BONDED TO THE DIELECTRIC
NOMINAL DIAMETER OVER TAPE: 0.287" (7.29 mm)
2ND SHIELD: 34 AWG ALUMINUM BRAID WIRE
60% COVERAGE
3RD SHIELD: ALUMINUM LAMINATED TAPE
4TH SHIELD: 34 AWG ALUMINUM BRAID WIRE
40% COVERAGE

JACKET:

PE JACKET (FLOODED FOR UNDERGROUND)
NOMINAL DIAMETER OVER JACKET: 0.407" (10.34 mm)
NOMINAL JACKET THICKNESS: 0.037" (0.94 mm)



ELECTRICAL PROPERTIES:

IMPEDANCE: 75.0 +/- 3.0 Ohms
VELOCITY OF PROPAGATION: 85.0% NOMINAL
ATTENUATION @ 68°F (20°C):

Shipping Weight (Lbs.)/1000': 64 lbs.

@ Frequency MHz	dB/100 ft. (MAX.)	dB/100 meters (MAX.)
5 MHz	0.38 dB	1.25 dB
55 MHz	0.96 dB	3.15 dB
83 MHz	1.18 dB	3.87 dB
187 MHz	1.75 dB	5.74 dB
211 MHz	1.90 dB	6.23 dB
250 MHz	2.05 dB	6.72 dB
300 MHz	2.25 dB	7.38 dB
350 MHz	2.42 dB	7.94 dB
400 MHz	2.60 dB	8.53 dB
450 MHz	2.75 dB	9.02 dB
500 MHz	2.90 dB	9.51 dB
550 MHz	3.04 dB	9.97 dB
600 MHz	3.18 dB	10.43 dB
750 MHz	3.65 dB	11.97 dB
865 MHz	3.98 dB	13.05 dB
1000 MHz	4.35 dB	14.27 dB



Drawing not to scale.
Specifications subject to change.
Revision: 03/08/07